

Mt. Lawn Speedway

2017

UPDATE 2/17/17

Thunder Car Rules

The absence of a particular rule does **NOT** necessarily mean its approval!

FRAME

1. Any 1968 and newer, full frame, rear wheel drive full sized car, with a stock wheelbase from 108" to 116" except **NO** Camaro, Firebirds or Mustangs and no Monte Carlo type frames older than 1978
2. Frames must remain OEM.
 - A. No cutting, sectioning, notching or modifying of frame allowed.
 - B. 2 x 3 rectangle steel stock may replace the rear tail at a point from the center of the rear end back. This material must retain stock height and configuration of the OEM frame.

BODY

1. Complete bumper to bumper steel body must be retained.
2. **NO** T-tops.
3. All doors must be welded, chained or bolted shut.
4. All glass, headlights, taillights, and mirrors must be removed.
5. Full front **LEXAN** windshield is required.
6. All bumpers must be secured by means other than OEM (Extra bolts, chains or welded in place).
7. Front and rear bumpers can be replaced by structural steel no larger than 2 inch x 3 inch in size and no wider than the center line of the tires. A radiator hoop and fuel cell hoop may be attached to it.
8. Spoilers are prohibited.

INTERIOR

1. The OEM **complete** steel floor pan and front firewall must be retained to and including the rear firewall and located in **stock** location.
2. The only modifications allowed to the floor pan and front firewall are to repair rusted places and patch holes.
3. Front wheel wells, ½ the rear wheel wells, and trunk floor may be removed.
4. The stock steering column may be replaced with aftermarket tubing, heims, u-joints and column supports. A collapsible steering shaft is highly recommended. **NO** straight steering shafts (from box to steering wheel) must have a minimum one u-joint.

5. Switch and push button may replace key switch.
6. One battery box must be securely mounted outside the driver's compartment or be securely mounted, covered and behind driver's seat.

ROLL CAGE

1. All cars must have a roll cage that includes four corner posts, **roof high** that are connected to the top and welded to the frame at the bottom.
2. Cage center section must be braced back to the rear frame rails.
3. Roll cage must be centered on the OEM frame rails. Top halo must be full, no half or three quarter cages or halos. Top halo must fit tightly against the roof. **NO** dropped cages. Main hoop behind driver must be mounted a minimum of **32** inches from centerline or rear hub to back of cage.
4. All cars must have four door bars on the left side that arch out to the door skin and at least two straight bars on the right side. All joints must be properly welded.
5. All cages must have a 1/8 inch thick aluminum plate or 1/8 inch steel plate on the outside of the driver's door bars, running from frame rail to top door bar and from door post to door post.
6. All roll cage tubing must be a minimum 1 3/4 inch OD and a minimum .095 wall thickness. **NO Muffler Tubing.**
7. **NO** bars off top halo forward to the right/left front hoop.
8. All roll cage installations are subject to Tech inspection and approval.

FRONT SUSPENSION

1. **All** suspension MUST remain in stock, **UNALTERED LOCATION** and be of stock components. No offset suspension components of any kind may be used. **Frame and suspension may not be added to or altered.**
2. Maximum 3 inch stem on all ball joints, measured from top of base to top of stem. **NO** dust boots.
3. **NO** adjustable eye bolt sway bars. OEM stock type bars mounted in stock location maximum diameter of 1.25 inches.
4. **NO** heim joint tie rods or sleeves, OEM stock only.
5. Maximum tread width of 78 inches measured outside of tire to outside of tire. Wheel spacers are OK to use.
6. Aftermarket coil springs and shocks, mounted in stock location, are allowed. **NO TAKE APART SHOCKS.** Steel body, stock appearing and stock mounting shocks **ONLY.**
7. Minimum frame height at any point on the car must be 6" inches at all points

REAR SUSPENSION

1. Aftermarket coil springs and shocks, mounted in stock location, are allowed. **NO TAKE APART SHOCKS.** Steel body, stock appearing, and stock mount shocks **ONLY.**
2. Jack bolts and spring cups are allowed on **rear** only.
3. OEM rear end housing must be used for the make and model of car being used. **NOTE:** 9" Ford rear end differentials allowed in non -ford cars. floaters will be

allowed. upper and lower trailing arms must be stock OEM, stock mount, in stock location with NO adjustable tubler trailing arms and no heim ends allowed.

4. Any available gear ration my be used.
5. Rear end differential may be open, positive or locked.
6. OEM rear trailing arms and top links with stock type bushings.
7. Minimum frame height at any point on the car must be 6”

DRIVE LINE

1. All cars must use an OEM automatic transmission with a working reverse. Must have a working stock appearing torque convertor.
2. Standard tranmissions (stick) are allowed with a stock clutch and a stock pressure plate. **NO racing clutch or pressure plate allowed. If a standard transmission is used there will be a 50 lb. weight penalty.**
3. Drive shaft and yokes must be made of steel and painted white.
4. All standard transmission bell housings must have an inspection plate.

BRAKES

1. Brakes must be OEM.
2. Cars must have functional brakes on all four (4) wheels.
3. **NO** Aftermarket Pedals or Master Cylinders allowed.
4. **NO** brale bias devices allowed.

ENGINE

1. The 2nd plug on the left side of the engine must be located within 1 inch of the center of the ball joint.
5. **Aluminum or cast iron intakes, cylinder heads and block must be cast iron. If aluminum intake is used there will be a 50 lb. weight penalty.**
2. Twenty-three (23) degree cast iron cylinder heads are permitted.
3. **NO** interchanging engines between makes. Engine must be of same corporation as frame and body.
4. Any Holley or Rochester carb allowed. **NO** Dominators.
5. Carb spacers allowed 1 inch maximum.
6. Ignition system must remain completely OEM.
7. **NO** aftermarket distributors, MSD boxes or add on electronic amplifiers.
8. Aftermarket aluminum radiators OK, mounted in the stock position.
9. NO antifreeze allowed. **IF** detected the penalty is disqualified for the night no money no points.
10. Radiator overflow hose must exit at right side windshield.
11. All cars must have OEM cast iron exhaust manifolds. **NOTE:** Headers are allowed but may not be cross over or 180’s . **NO GRASS BURNERS. If headers are used there will be 25 lb. weight penalty.**
12. Exhaust must exit behind driver, within 18 inches of the rear end housing.
13. Maximum 2 exhaust pipes with OD no larger than 3 ½ inches.
14. **NO** NASCAR exhaust.
15. **NO** Roller Cams.Roller Rockers permitted
16. **NO** oil coolers allowed inside drivers compartment.

WHEELS/TIRES

1. All cars must use a maximum 8 inches wide, steel, racing wheel. Racing wheels are encouraged.
2. NO magnesium, aluminum or slotted wheels allowed.
3. **Hoosier Comanche** or any 15" or 16" D.O.T. 60,70,75 series radial tire may be used on a maximum of an 8" wide steel wheel. One Goodyear (2864 or 2865) available from the track at \$20 per tire may be used in any position.

FUEL CELL

1. All cars must have a made for racing fuel cell.
2. Fuel cells shall be securely mounted as far forward as possible, between the OEM frame rails and no less than 10 inches off the ground.
3. Fuel line may **NOT** pass through the driver's compartment.
4. DOT pump gas or approved racing fuel only.
5. **NO** electric fuel pumps.

WEIGHT

1. Minimum weight 3200lbs with driver.
2. All ballast must be painted white and securely mounted with the car number on it.
- 3.

SAFETY

1. All cars must have an approved aluminum seat, mounted securely to the frame and cage. **NO** plastic or fiberglass seats.
2. All cars must have an approved five point seat belt assembly, minimum of 3" inches wide, less than 3 years old and securely bolted to the frame and cage.
3. A Hans, Hutchens or Neck collar is mandatory.
4. A Snell 95 SFT or higher helmet is mandatory.
5. A minimum single layer one or two piece fire suit is required, with gloves.
6. Fire Bottle is highly recommended. Fire Extinguisher is mandatory.
7. An approved window net is required, with the latch at the top/front.
8. **NO** mirrors. ALL mirrors must be removed. **NO** radios.
9. All safety equipment and installation must be approved by Tech.

DEFINITIONS

1. STOCK – A part that was mass produced for the automotive industry.
2. OEM – AS it was produced by the Original Manufacturer for the make model and year of the particular car or style of car.
3. STOCK TYPE - Aftermarket part similar in design and functions as the stock OEM part.

4. **NO MEANS NO.**

OVERALL

NONE OF THESE RULES ARE MEANT TO IMPLY OR GUARANTEE IF FOLLOWED, THESE SAID RULES WILL PREVENT INJURY OR DEATH.

1. THE INTERPRETATION OF THESE RULES IS LEFT TO THE DISCRETION OF THE TRACK TECH OFFICIALS.
2. RACE TRACK RESERVES THE RIGHT TO CHANGE, MODIFY, ADD OR DELETE TO THESE RULES AT **ANY** TIME AS THEY DEEM NECESSARY TO ENSURE **FAIR, COMPETITIVE AND AFFORDABLE RACING.**
3. ALL DECISIONS OF THE TECH OFFICIALS ARE **FINAL** AND BINDING WITHOUT EXCEPTION.
4. **THE CAR DRIVER IS RESPONSIBLE FOR ALL CREW MEMBERS AT ALL TIMES.**

IF YOU HAVE QUESTIONS YOU MAY CONTACT TECH INSPECTOR MIKE STONE 765-623-4200 OR JEFF VAN HOY 765-345-5416.